HPG 70-K

Fully insulated, portable HV test system up to 70 kV DC



- Highest level of safety due to the fully insulated design
- Compact and lightweight
- Separate control and HV unit
- Continuously adjustable voltage
- Measures HV potential

DESCRIPTION

The HPG 70-K HV test set is a fully insulated system for DC testing up to 70 kV. Thanks to its fully insulated design, this system is ideal for stand-alone applications. The DC voltage is obtained through a bridge rectifier which ensures a very low ripple in the test voltage. Moreover, the DC voltage is measured on the secondary side, ensuring a precise output voltage.

The HPG 70-K consists of two units and is used for testing cable installations as either a stand-alone system or built into a module or cable test van.

The control unit HSG 1 includes a variac. Its output voltage feeds the high voltage unit HVT 70-K.

The HVT 70-K is fully insulated: the test voltage of 70 kV DC is drawn from a socket outlet and fed to the cable under test. A multi-pole connection lead is supplied to feed the control voltage of 0-230 V AC.

TECHNICAL DATA*

HPG 70-K

 $\begin{array}{lll} \textbf{DC output voltage} & 0 \dots 70 \, \text{kV} \\ \textbf{DC output current} & 0 \dots 10 \, \text{mA} \\ \end{array}$

 Measuring ranges
 0.1, 1, 10 mA

 Timer
 0 ... 60 min

 Dimensions control unit
 520 x 255 x 320 mm

Weight control unit 18 kg

Dimensions HV unit 320 x 255 x 255 mm

Weight HV unit 21 kg

Power supply 230 V \pm 10 %, 45 ... 60 Hz,

700 VA

Operating temperature $-25 ... +55 ^{\circ}$ C Storage temperature $-40 ... +85 ^{\circ}$ C

ALL ADVANTAGES AT A GLANCE

- Highest level of safety thanks to the fully insulated design
- Compact and lightweight
- Separate control and HV unit
- Voltage continuously adjustable
- Measurement at HV potential

ORDERING INFORMATION	
Product	Order no.
HPG 70-K	813226
Control unit HSG 1, HV-unit HVT 70-K, set of cables, discharge rod 75 kV	

SALES OFFICES

Megger GmbH

Obere Zeil 2
D-61440 Oberursel
Germany
T 0049 6171 92987-0
E info@megger.de

Seba Dynatronic Mess- und Ortungstechnik GmbH Dr.-Herbert-lann-Str. 6 96148 Baunach Germany T 0049 9544 68-0

E team.international@megger.de

HPG70K_DS_EN_V02

www.megger.com ISO 9001

The word 'Megger' is a registered trademark.



 $[\]ensuremath{^{\star}}$ We reserve the right to make technical changes.